

DRAWN CHECKED DATE

REVISION / DESCRIPTION

DRAWN CHECKED DATE





BUILDING DESIGN PARTNERSHIP SHALL HAVE NO RESPONSIBILITY FOR ANY USE MADE OF THIS DOCUMENT OTHER THAN FOR THAT WHICH IT WAS PREPARED AND ISSUED.

ALL DIMENSIONS SHOULD BE CHECKED ON SITE.

DO NOT SCALE FROM THIS DRAWING ANY DRAWING ERRORS OR DIVERGENCIES SHOULD BE BROUGHT TO THE ATTENTION OF BUILDING DESIGN PARTNERSHIP AT THE ADDRESS SHOWN BELOW. ONCE ELECTRONIC DATA IS INTRODUCED INTO YOUR IT SYSTEM, BDP CAN TAKE NO RESPONSIBILITY FOR ANY INACCURACY INTRODUCED THROUGH TRANSLATION. PAPER DRAWINGS CAN BE SUPPLIED SHOULD YOU REQUIRE THEM TO VALIDATE THE DATA. IF THE DATA IS ALTERED OR AMENDED IN ANY WAY BDP SHALL NOT BE RESPONSIBLE OR LIABLE FOR ANY OF THE DATA. IF THE DATA IS ALTERED OR AMENDED IN ANY WAY IT SHALL NOT BE REPRESENTED OR ISSUED IN ANY WAY THAT MAY ERRONEOUSLY LEAD IT TO BE CONSIDERED AS BEING PREPARED BY BDP AND BDP REFERENCES, LOGOS AND DRAWING NUMBERS SHALL BE REMOVED

NOTES

For full GA plan information at level 00 please refer to BDP drawings BDP_DAA_A(04)A101, 102, 103. For full GA plan information at level 01 please refer to BDP drawings BDP_DAA_A(04)A111, 112, 113. For full GA plan information at level 02 please refer to BDP drawings BDP_DAA_A(04)A121, 122, 123. For soction GA_A(04)A121, 122, 123. BDP_DAA_A(04)A121, 122, 123. For section GA information refer to BDP_DAA_A(04)401, 402, 403, 404, 405, 406, 407, 408, 409, 410. For elevation GA information refer to BDP_DAA_A(05)100, 101, 102, 103, 104, 105, 106, 107 For soffit and ceiling heights refer to (35) series drawings. For floor finishes refer to (43) series drawings. For fire strategy information refer to drawings (67) series drawings.

All structural steel to be 1 hr fire protected. All steelwork within external cavity walls to receive proprietary protective coating applied in accordance with manufacturers recommendations. All partitions to be lightweight studwork as BDP specification K10 and Knauf Specification unless otherwise noted. All partitions to span to u/s of structural soffit unless otherwise noted. All partitions to be Severe duty rated to BS 5231-1& 2:1992. 2.1992.
Internal lining to external walls generally 1 layer 60 minute fire rated board, unless noted as above. Vapour control layer and location of air tight line to be agreed with structural insulated panel supplier/sub-contractor.
All partitions to be installed in accordance with manufacturers recommendations.
Penetrations in partitions to be formed neatly and be sealed to maintain the acoustic participant back haves activate placetorized back haves activate placetorback. performance and fire rating. All electrical back boxes set into plasterboard to incorporate acoustic treatment. For location of wall mounted fixtures and fittings refer to C-Sheet (70) series drawings. Sub-contractor to advise and install all additional patresses/noggins etc as required for fixings of fixtures and fittings. Doors to corridors to be set out centrally to corridor unless dimensioned otherwise.

All penetrations through floor slab to be co-ordinated with BDP Architects, Structural Engineers and the steel frame/PPC floor sub-contractor. Please refer to M*E drawings for pipework types/sizes and routes. All drainage pipework to be insulated as required by M&E Specification and recommendations of acoustic report.

NOT FOR CONSTRUCTION **ISSUED FOR** INFORMATION ONLY

BDP.

Client Room Numbering and House Designation L0 BDP_DAA_A (04)500

Dixons Allerton Academy

P2002846

1:200 22.03.13 REVISION

@ A0